



Ezy-Guard 4 Data Sheet

Roadside Safety Barrier


MASHTL3 COMPLIANT

NCHRP-350 TL4 COMPLIANT

Features & Benefits

- Safer: Fully compliant to MASH TL3.
- h Performance: Demonstrated containment and re-direction of 2270kg pick-up truck travelling at 100km/h
- Fewer Parts: No blocking pieces or rail stiffener plates
- pid Installation: Fewer components facilitate rapid installation. Z-post embedment depth is just 880mm
- Cost Savings: Fewer components to purchase, savings on freight costs and faster to install
- Narrow Width: A system of just 200mm conserves valuable formation width







Ezy-Guard 4 Z-Post Length	1,650mm
Ezy-Guard 4 Z-Post Mass	12.5kg
Ezy-Guard 4 System Mass	18.6kg per metre
Rail Height Above Ground	787mm
Z-Post Height Above Ground	777mm
Post Spacing:	1,905mm
Ezy-Guard 4 System Width:	200mm
MASH TL3 Crash Test Deflection:	1.65m



Consideration for Vulnerable Road Users

The supporting Z-posts contain smooth, rounded post edges and corners. In addition, the revolutionary design of Ezy-Guard 4 shields the top of the support Z-posts by positioning the top of the rail above the posts. This eliminates a dangerous snag point and is a significant safety benefit compared to existing safety barrier designs.

Providing superior design, rapid installation, superior motorist safety and more metres of barrier for your dollar

www.ingalcivil.co.nz

Email: sales@ingalcivil.co.nz

Auckland

Orders: 021 246 4997 021 580 997 Bruce: Richard: 021 877 653

Christchurch

021 198 3311 lan: Steve: 021 480 753

Wellington

Brendon: 021 504 870