



Ezy-Guard Smart Data Sheet

Roadside Safety Barrier

Features & Benefits

- Safer: Fully compliant to MASH TL3.
- **High Performance:** Demonstrated containment and re-direction of 2270kg pick-up truck travelling at 100km/h
- Fewer Parts: No blocking pieces or rail stiffener plates
- Rapid Installation: Fewer components facilitate rapid installation. Z-post embedment depth is just 880mm
- Cost Savings: Fewer components to purchase, savings on freight costs and faster to install
- Narrow Width: A system of just 200mm conserves valuable formation width



Consideration for Vulnerable Road Users

The supporting Z-posts contain smooth, rounded post edges and corners. In addition, the revolutionary design of Ezy-Guard Smart shields the top of the support Z-posts by positioning the top of the rail above the posts. This eliminates a dangerous snag point and is a significant safety benefit compared to existing safety barrier designs.

Providing superior design, rapid installation, superior motorist safety and more metres of barrier for your dollar

MASHTL3 COMPLIANT







| Ezy-Guard Smart Z-Post Length | 1,600mm |
|---------------------------------|------------------|
| Ezy-Guard Smart Z-Post Mass | 12.3kg |
| Ezy-Guard Smart System Mass | 18.6kg per metre |
| Rail Height Above Ground | 730mm |
| Z-Post Height Above Ground | 720mm |
| Post Spacing: | 2,000mm |
| Ezy-Guard Smart System Width: | 200mm |
| MASH TL3 Crash Test Deflection: | 1.65m |

- Brisbane (07) 3489 9125 Melbourne (03) 9358 4100
- Perth (08) 9452 9111 Sydney (02) 9827 3333 Adelaide (08) 8169 2300
- Newcastle 0400 235 883
 Wagga 0427 779 588